

## **TORQUE LINK**

**SMART SENSOR TECHNOLOGY** 

### **RUGGED DESIGN**

MINIMAL LOSS OF HEADROOM

## **CLOUD STORAGE**

VIEW PILE LOGS ANYTIME, ANYWHERE





THE HARDWARE

Fabricated for serious jobs, our sleek designs protect the internals, and can accomodate most drives in the field.



#### Machined from SOLID BILLET

Ensuring maximum strength



#### Off-the-Shelf Batteries

Up to 400 hours working time



#### Bluetooth (BLE)

No loss of connection with high quality signal





#### **TORQUE SPOOLS**

#### **INQUIRE FOR BOLT MEASUREMENT**

MODEL	TORQUE	DIAMETER	HEIGHT
SP-030	30K	9"	7"
SP-070	70K	10.25"	8"
SP-250	250K	11"	11"
SP-375	375K	11"	11"



#### **TORQUE HUBS**

MODEL	HEX INPUT	SPECS	
HB-030-2HX	2"	TORQUE RATING	30K
HB-030-2.5HX	2.5"	FLANGE	9"
HB-030-2.625HX	2-5/8"	BOLT PATTERN	5-1/4", 7-5/8"
HB-030-3HX	3"		

**HB-070: 100mm (4") SQUARE INPUT HUB** 




#### **TORQUE LINKS (M-F)**

#### MODEL

MF-030-2HX MF-030-2.5HX MF-030-3HX

SPECS	
TORQUE RATING	30K
LENGTH (HOLE TO HOLE)	9-1/8"



**70K RATED** 

# **FEATURES**



Bay 108, 239 Spruce Street Red Deer County, Alberta Canada T4E 1B4 Jim: 403-318-3294 Office: 403-309-2220 Email: jim@alltorque.ca

Fax: 403-346-1410 Email: info@alltorque.ca